

Software Product Description

PRODUCT NAME: HP ACMS for OpenVMS, Version 5.0A 82.40.02

DESCRIPTION

This document addresses HP ACMS Version 5.0A for OpenVMS Alpha Systems and HP ACMS Version 5.0A for OpenVMS Industry Standard 64 (I64) for Integrity servers.

HP Application Control and Management System for OpenVMS (ACMS) is a transaction processing (TP) monitor designed for the HP OpenVMS operating systems. ACMS works with other HP commercial application software products to provide users with a complete and customizable development and run-time environment for transaction processing applications such as order tracking, accounting and billing, banking, shop floor control, and insurance claims processing.

ACMS software helps users through the entire application development life cycle, including the installation, planning, design, development, testing, implementation, management, and maintenance of complex TP applications. ACMS provides a special-purpose application definition language for the structured definition of TP application functions and run-time characteristics.

ACMS makes efficient use of the OpenVMS operating systems and associated hardware resources, making ACMS particularly suited to mission-critical applications that require high throughput and performance.

ACMS integrates with the following HP and third-party layered products:

- HP TP Desktop Connector, formerly called ACMS Desktop, for multivendor client access to ACMS applications
- HP TP Web Connector for Web browser-based access to ACMS applications

- HP TPware .NET Plugin
- HP DECforms or HP TDMS for forms management
- All OpenVMS languages that conform to the OpenVMS Calling Standard
- Oracle CDD for the creation, analysis, and administration of metadata
- Oracle Rdb, Oracle CODASYL DBMS, and OpenVMS RMS for data management
- Oracle Trace for performance event data collection

Because ACMS is designed to allow for modular implementation as well as development, the client/server model can be used to separate and distribute frontend processing (data input/output operations such as forms processing) from back-end processing (data calculations and database storage). In addition, ACMS allows users the use of nonstandard terminal or I/O devices, such as bar-code readers and automatic teller machines (ATMs).

Features

ACMS provides the following features:

- Application development environment
- Run-time system
- Application management and control
- Remote system management
- Client/server processing
- Presentation services
- Database management
- Resource utilization collection and reporting

- Task queuing
- Data dictionary
- Security
- OpenVMS Cluster environment and availability

Application Development Environment

ACMS uses a high-level, English-like definition language that replaces system service calls for most TP application functions. Using the ACMS Application Definition Utility (ADU), a programmer can:

- Structure all application work into three basic steps:
 - Exchange steps for terminal I/O processing
 - Processing steps for database access and general computation
 - Block steps for performing work common to several processing and exchange steps
- Control task execution and flow using conditional statements such as IF THEN ... ELSE, WHILE DO, SELECT FIRST, and CONTROL FIELD syntax in conjunction with Boolean expressions.
- Define and implement subroutine transactions using the CALL TASK syntax.
- Create menus and hierarchies of menus.
- Define resources used to execute transactions, such as servers, workspaces, and audit trails.
- Start and end database recovery units.

ACMS also includes the ACMS Task Debugger to debug ACMS definitions and servers.

Run-Time System

ACMS includes a complete run-time system for application deployment. The ACMS Run-Time System consists of eight specialized processes.

The following ACMS processes manage the work within ACMS transactions:

- Command Process (CP) Manages logins and interaction between terminals and ACMS. CPs are multithreaded (one CP process can handle menus and forms I/O for many ACMS terminals simultaneously). The CP passes input data to the Application Execution Controller (EXC) for processing by a server.
- Application Execution Controller (EXC) Controls task execution for all the tasks in an application. Each application has its own EXC process, which starts up and controls the server processes needed to handle processing work for tasks.

- Server Process (SP) Carries out the high-level programming language routines or DCL routines that handle a task's processing work and database or file I/O. Programmers link their routines to the ACMSsupplied main program to create customized servers for database access, computation, and other functions.
- Queued Task Initiator (QTI) Removes task elements from a task queue and initiates their execution in a specified application. Queued tasks are tasks placed in a queue for later execution. Queued tasks cannot collect terminal input data; otherwise they are the same as any other ACMS task.

The ACMS processes that monitor and control the runtime system are:

- ACMS Central Controller (ACC) Acts as the central control point for ACMS run-time systems. The ACC starts and controls the Terminal Subsystem Controller, the QTI, the EXC, and the audit trail log. The ACC process must be started and running on each computer system where ACMS applications are used.
- Audit Trail Logger (ATL) Writes information about a running ACMS system to the audit trail log file. The ATL keeps a record of when the ACMS system starts and stops, when users log in, and when applications and tasks start and stop.
- Terminal Subsystem Controller (TSC) Creates and controls the number of active Command Processes (CPs) and assigns terminals to CPs. The TSC starts and stops CPs as needed, and controls which terminals can access ACMS.
- Software Event Logger (SWL) Records all ACMS internal software errors and event messages that occur during the execution of ACMS application programs.

Communication among these run-time processes can occur on a single computer system, or between more than one computer in a OpenVMS Cluster system or DECnet network. For example, a Command Process (CP) on one computer system can initiate a task within an application on another computer system.

Application Management and Control

Once an application is developed, the user moves that application into a production (real-use) environment. ACMS provides support for ACMS applications used in a production environment.

ACMS includes seven utilities for defining, monitoring and modifying application management characteristics:

• ACMSGEN — Modifies and displays ACMS system parameters.

- Application Authorization Utility (AAU) Authorizes applications to be installed.
- User Definition Utility (UDU) Authorizes users to log in to ACMS and assigns login displays, including default menus, to ACMS users.
- Device Definition Utility (DDU) Authorizes ACMS terminals and, optionally, defines captive terminals to log in directly to ACMS.
- Queue Manager (QUEMGR) Creates and manages ACMS task queues and queued task elements.
- Software Event Log Utility Program (SWLUP) Creates reports of selected events recorded by the Software Event Logger.
- Audit Trail Report Utility (ATR) Returns records of application and user activity.

In addition to the utilities, ACMS also provides users with the following support for application management and control:

- ACMS operator commands Performs standard operator functions such as starting and stopping the ACMS system, the TSC process, the QTI process, and ACMS applications.
- Command procedures Evaluates and modifies the values of OpenVMS and ACMS system parameters and of ACMS run-time process quotas.

Remote System Management

The ACMS Remote Manager provides the capability to monitor and manage the ACMS application environment. ACMS system managers can access the Remote Manager using one of the supported interfaces over a TCP/IP network.

The Remote Manager must be running on the same node as the ACMS run-time system it is monitoring or accessing. Communication between the Remote Manager and the ACMS run-time system is transparent.

Three interfaces allow access to the Remote Manager:

- RPC Interface—Provides local or remote access to ACMS management information using the Open Network Computing Remote Procedure Call (ONC RPC) protocol. This interface can be used by user-written programs to implement customized ACMS management tools.
- Command Line Utility—Provides command line access to management information as well as control of the Remote Manager process. This utility uses the RPC Interface.

 Simple Network Management Protocol (SNMP) Interface—Provides network access to ACMS management information using the industry standard SNMP protocol. This protocol is supported by most system management consoles and tools.

ACMS system managers control the data being collected, including ACMS process monitoring, and the management interfaces themselves through either SNMP or RPC commands.

The Remote Manager enables ACMS system managers to do the following:

- Remotely manage agents, including user-written agents, HP-supplied agents (such as HP TP Web Connector, HP TP Desktop Connector and HP TPware .NET Plugin), and agents supplied by other vendors.
- Remotely manage data collection including configuring SNMP traps and viewing management information on line.
- · Remotely modify ACMS run-time systems.
- Write programs that remotely access management information online using ONC RPC and SNMP.

Client/Server Processing

ACMS uses the client/server model to distribute and separate functions. This model can be implemented on a single node or on multiple nodes in a DECnet network.

The terminal and menu functions are handled on the client, or front end, of the transaction processing system, while task flow control, data processing, and computations are performed on the server, or back end, of the system.

Because the ACMS client/server model always provides separate front and back ends, users can at any time offload the front-end to another computer system without reprogramming the application code.

The ACMS Systems Interface (SI) lets users write front end programs, or agents, to support specialized devices such as bar-code readers and automatic teller machines.

ACMS includes support for failover in a distributed environment. If one OpenVMS node is not available to process a transaction, ACMS can automatically route the transaction to another application running on an available node.

Presentation Services

ACMS supports both terminal-driven and PC/workstationdriven TP applications with presentation services. Users have the option of running ACMS tasks from menus on VT terminals, or from a GUI interface on a PC/workstation desktop system.

ACMS supports DECforms as its primary presentation service for character-cell terminals in ACMS applications. In addition, ACMS provides support for HP TDMS. ACMS applications that use TDMS must be distributed in order to use ACMS on OpenVMS Alpha. See the *HP ACMS for OpenVMS Writing Applications* manual for more information about these restrictions.

The TP Desktop Connector and TPware .NET Plugin provides an API that allows user-written program running on various PC or workstation desktop systems to initiate and respond to ACMS tasks. A wide range of HP and third-party desktop tools can be used for the development of client presentation services and applications.

ACMS also provides support for other presentation service products through the ACMS Request Interface and Systems Interface. The Request Interface lets users use presentation services other than DECforms or TDMS for I/O functions limited to one user per process. The Systems Interface lets users use presentation services for single-user or multiple-user I/O functions.

Database Management

ACMS includes support in its definition language for starting and ending database transactions/recovery units through a database management system. Database products supported include Oracle Rdb (including SQL), RMS, and Oracle CODASYL DBMS.

Using the DECdtm component of the OpenVMS operating system, ACMS lets users coordinate operations on multiple recoverable resources (such as databases and files) within a single atomic transaction. Users can perform operations on multiple databases through a single transaction and ensure atomicity (that is, if the transaction fails, any changes made to databases, files, or ACMS queues are rolled back to their previous state before the transaction started). Please note that RMS Journaling for OpenVMS is required to support recoverable ACMS queue operations coordinated using DECdtm. RMS Journaling for OpenVMS is a separate layered product, distinct from RMS, and is supplied with OpenVMS.

ACMS applications can also access other data management products or file management systems that support the OpenVMS Calling Standard.

Resource Utilization Collection and Reporting

ACMS supports Oracle Trace to allow the collection and reporting of event-based data gathered from any combination of OpenVMS layered products and ACMS applications. For each predefined event in ACMS, Oracle Trace can collect information about resource utilization, such as CPU time, or ACMS data items, such as task name. Using the Oracle Trace cross-facility feature, you can relate ACMS events with events from multiple layered products.

Task Queuing

Some ACMS applications require that the data be collected and stored in a temporary storage area (queue) for the application to process at another time. The ACMS queuing facility lets users create and manage ACMS task queues. ACMS queue services are used to place/remove tasks on/off ACMS task queues.

Data Dictionary

ACMS supports the Oracle CDD/Repository data dictionary. ACMS stores application definitions in Oracle CDD/Repository directories and uses Oracle CDD/Repository record definitions for its workspaces.

Security

ACMS ensures that the user's data remains secure by giving the system manager control over which users have access to ACMS. Using OpenVMS and ACMS authorization facilities, system managers can:

- Authorize users to use ACMS.
- · Control terminals connecting to ACMS.
- · Limit the applications a user can run.
- Prevent unauthorized access to the operating system while running ACMS tasks.

ACMS includes transaction security in the form of access control lists (ACLs) in the definition language. Whenever a user selects a transaction, that user's OpenVMS identifier is checked against the ACL defined for that transaction to determine whether that user is allowed to execute that transaction.

OpenVMS Cluster Environment/Availability

In a OpenVMS Cluster environment, ACMS applications support highly available configurations that help avoid single points of system failure.

ACMS includes support for failover in a OpenVMS Cluster environment. If one OpenVMS Cluster processor is not available to process a transaction, ACMS can automatically route the transaction to another application running on an available processor that shares the same data. ACMS can improve the performance of a database management system in a OpenVMS Cluster environment by allowing the use of the client/server model to run database servers on a single processor.

Documentation

ACMS includes a complete and comprehensive documentation set:

- An introductory manual explains ACMS concepts and components to new users.
- Advanced manuals describe, in a task-oriented style, how to design, build, and manage ACMS applications.
- Complete reference information is provided.

The ACMS Development System documentation set consists of the following manuals:

- Getting Started
 - Provides an introduction to the basic elements of the ACMS transaction processing system.
 - Provides a step-by-step tutorial for developing a simple ACMS application.
 - Provides an overview of the AVERTZ sample application.
 - Provides a glossary of ACMS terms.
- Concepts and Design Guidelines
 - Describes how to design an ACMS application.
- Writing Applications
 - Describes how to write task, task group, application, and menu definitions using the Application Definition Utility (ADU).
 - Describes the input/output options and restrictions in a distributed environment.
 - Describes how to write and migrate ACMS applications to OpenVMS Alpha systems.
- Writing Server Procedures
 - Describes how to write programs for use with tasks and how to debug tasks and programs, including how to write procedures that access databases.
 - Describes how ACMS works with the APPC/LU6.2 programming interface to communicate with IBM CICS applications.
- Systems Interface Programming
 - Describes how to use Systems Interface (SI) Services to submit tasks to an ACMS system.

- Managing Applications
 - Describes how to authorize, install, run, and manage ACMS applications, and how to control the ACMS system.
- Remote Systems Management Guide
 - Describes the features of the Remote Manager for managing ACMS systems, how to use the features, and how to manage the Remote Manager.
- ADU Reference Manual
 - Provides reference information about the ADU commands, phrases, and clauses.
- ACMS Version 5.0A Installation Guide
 - Describes installation requirements, step-by-step installation instructions, and required post-installation tasks.
- Quick Reference Guide
 - Provides a complete list of ACMS syntax with brief descriptions.
- Release Notes
 - Provides late-breaking and other notable online information about the latest release of the software.
- Online Help
 - Provides online help about ACMS and its utilities.

HARDWARE REQUIREMENTS

Hardware Configurations

ACMS Version 5.0A is supported on all hardware configurations referenced in the *OpenVMS Operating System for Alpha, Version 8.2 or later, Software Product Description* (SPD 82.35.xx) and *OpenVMS Operating System for 164, Version 8.2-1 or later, Software Product Description* (SPD 82.35.xx)

Disk Space Requirements (Block Cluster Size = 1)

The approximate amount of space required on the system disk to support the ACMS for OpenVMS software is as follows. Actual sizes may vary depending on the system environment, configuration, and software options.

ACMS Kit	Alpha	164
Development Installation	70,000 blocks 35.0 Mbytes	83,000 blocks 41.0 Mbytes
Development Permanent	42,000 blocks 21.0 Mbytes	50,000 blocks 25.0 Mbytes
Run-Time Installation	38,000 blocks 19.0 Mbytes	74,000 blocks 37.0 Mbytes

ACMS Kit	Alpha	164
Run-Time Permanent	33,000 blocks 16.5 Mbytes	40,000 blocks 20.5 Mbytes
Remote Installation	27,000 blocks 13.5 Mbytes	56,000 blocks 28.0 Mbytes
Remote Permanent	24,000 blocks 12.0 Mbytes	40000 Blocks 20.50 Mbytes

SOFTWARE REQUIREMENTS

HP ACMS for OpenVMS, Version 5.0A software runs on the following versions of the OpenVMS operating system:

- OpenVMS Alpha Operating Systems Version 8.2 or later.
- OpenVMS I64 Operating Systems Version 8.2-1 or later.

Specific versions of networking software are supported for each version of the operating system. See the following sections for the supported versions.

O/S Version	HP TCP/IP Services for OpenVMS Version
Alpha V8.2 or later	V5.6
164 V8.2-1 or later	V5.6

The following versions of Oracle CDD/Repository is required that is supported on your version of the operating system as follows:

- OpenVMS Alpha requires V7.0 and above
- OpenVMS I64 requires V7.2 and above

Note: When using ACMS with HP DECnet-Plus for OpenVMS (formerly called DECnet/OSI), the Transport Layer must be configured to use the Network Services Protocol (NSP). ACMS restricts node names to a maximum of six characters.

OPTIONAL SOFTWARE

Certain versions of these products depend on a specific version of the operating system. Please refer to the Software Product Description (SPD) or contact the vendor for the product in question to determine which version is required for correct operation.

Software	OpenVMS Alpha	OpenVMS I64
HP DECforms	V3.3	V4.0
HP DECset	V12.7	V12.7
HP LSE	V5.0	V5.0
HP TP Desktop Connector	V5.0A	V5.0A
HP TP Web Connector	V5.0A	V5.0A
Oracle CDD/Repository	V7.0	V7.2
Oracle Rdb	V7.2-1	V7.2-1
HP TPware .NET Plugin	V5.0	V5.0
Oracle Trace	V7.2(optional)	V7.2(optional)

SOFTWARE LICENSING

This software is furnished only under a license. For more information about licensing terms and policies from HP, contact your local HP office.

LICENSE MANAGEMENT FACILITY (LMF)

This layered product supports the OpenVMS License Management Facility.

ACMS for OpenVMS Alpha

License units for the Development System are allocated on a Capacity Basis by hardware tier. License units for the Run-Time or Remote Systems are allocated on a Capacity Basis by hardware tier or a Concurrent Use basis.

For more information on the OpenVMS License Management Facility, refer to the OpenVMS Operating system for Alpha Software Product Description (SPD 82.35.xx) or documentation.

ACMS for OpenVMS I64

ACMS for OpenVMS I64 software product licenses are sold on a per-processor core license (PCL) basis.This layered product supports the OpenVMS License Management Facility of HP.

ACMS products are PCL licensed with one license required for each active physical processor core in the system of hard partition. If additional processors are later added to the system of hard partition, each requires an additional PCL.

For more information on the OpenVMS License Management Facility, refer to the OpenVMS Operating system for I64 Software Product Description (SPD 82.35.xx) or documentation.

CLUSTER ENVIRONMENT

This layered product is fully supported when installed on any valid and licensed OpenVMS Cluster configuration without restrictions. The Hardware Requirements section of this Software Product Description details any special hardware required by this product.

OpenVMS Cluster configurations are fully described in the *OpenVMS Cluster Software Software Product Description* (SPD 29.78.xx) and include CI, Ethernets and mixed-interconnect configurations.

DISTRIBUTION MEDIA

ACMS for OpenVMS Alpha is available on the Open-VMS Alpha Software Product Library Package. The ibrary package includes media and documentation on CD-ROM.

ACMS for OpenVMS I64 is available on the OpenVMS Layered Product Library. The library package includes media and documentation on CD-ROM.

Updates for ACMS for OpenVMS I64 are delivered through software updates services. The Layered Products Library is included in the original Operating Environment Media purchase, but is not separately orderable.

ORDERING INFORMATION

Three kits are available for ACMS:

- ACMS Development System—The complete set of ACMS features that facilitate the development and deployment of ACMS applications on an OpenVMS system.
- ACMS Run-Time System—A subset of the ACMS Development System that allows the deployment and limited customization of ACMS applications on an OpenVMS system.
- ACMS Remote Access—A subset of the ACMS Run-Time System that provides the capability to place users and the associated terminal I/O on a separate OpenVMS system to offload the application system or OpenVMS Cluster.

For OpenVMS Alpha	Part Number
Development License, Unlimited Use	QL-2PZA*-AA
Development Documentation	QA-076AA-GZ
Development Software Product Services	QT-2PZA*-**

* Denotes variant fields. For additional information on available licenses, services, and media, refer to the appropriate price book.

Run-Time License, Unlimited Use

Run-Time License. Concurrent Use

Run-Time Software Product Services

Remote Access, Unlimited Use

Remote Access. Concurrent Use

Remote Access Documentation

Remote Access Software

Product Services

Run-Time Documentation

For OpenVMS I64	Part Number
HP ACMS Development VMS I64 PCL LTU	BA339AC
HP ACMS Development VMS I64 Media	BA339AA*
HP ACMS Development documentation (hardcopy)	BA339MN
HP ACMS Runtime VMS I64 PCL LTU	BA341AC
HP ACMS Runtime VMS I64 Media	BA341AA*
HP ACMS Runtime documentation (hard- copy)	BA341MN
HP ACMS Remote VMS I64 PCL LTU	BA340AC
HP ACMS Remote VMS I64 Media	BA340AA*
HP ACMS Remote documentation (hard- copy)	BA340MN

* Include in any order where software updates are planned.

SOFTWARE PRODUCT SERVICES

A variety of service options are available from HP. For more information, contact your local HP office.

GROWTH CONSIDERATIONS

The minimum hardware/software requirements for any future version of this product may be different from the requirements for the current version.

SOFTWARE WARRANTY

This software is provided by HP with a 90-day conformance warranty in accordance with the HP warranty terms applicable to the license purchase.

QL-2Q1A*-AA

QL-076AA-3B

QA-076AA-GZ

QT-2Q1A*-**

QL-2Q0A*-**

QL-Y30AA-3B

QA-Y30AA-GZ

QT-2Q0A*-**

HP ACMS for OpenVMS, Version 5.0A

The above information is valid at time of release. Please contact your local HP office for the most up-to-date information.

© Copyright 2006 Hewlett-Packard Development Company, L.P.

Confidential computer software. Valid license from HP required for possession, use or copying. Consistent with FAR 12.211 and 12.212, Commercial Computer Software, Computer Software Documentation, and Technical Data for Commercial Items are licensed to the U.S. Government under vendor's standard commercial license.

The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.